


# SL-3<sup>®</sup>

SENSOR

## Vibration (Shaker) Sensor Line



- Adjustable super sensitivity
- Maintenance free
- Positive Attitude Recognition (PAR)<sup>™</sup>
- Automatic self-cleaning contact points
- Suitable for any type of fence or wall



# SL-3<sup>®</sup>

SENSOR

The **SL-3** Multidirectional Vibration (shaker) Sensor Cable is a patented system which supersedes and outperforms all types of fence sensor technologies.



**SL-3** Multidirectional vibration (shaker) sensor cable is an advanced, highly reliable intrusion detection system. Its unique capability provide for super sensitivity and accurate responses to vibrations caused by intrusion attempts.



The **SL-3** sensor cable is factory pre-assembled with sensors at 3 meter (10') intervals. Installation of the **SL-3** Sensor Cable is fast and simple to install, as it is supplied ready for mounting to any new or existing type of perimeter barrier such as; chain link, welded mesh, razor tape coil, concrete or block walls and roof-tops.

Due to its advanced design and configuration, the field proven **SL-3** Sensor Cable has a high Probability of Detection (Pd) rating and an extremely low False Alarm Rate. The **SL-3** sensor cable is maintenance free and warranted to be free from defect and/or sensor failure for a period of not less than 10 years.



## SPECIFICATIONS:

- **Operating temp:** -45°C (-49°F) to +70°C (+158°F).
- **Capsule Enclosure:** Injection molded high resistant plastic
- **Size of capsule:** 69 x 42 x 30mm (2.7" x 1.65" x 1.18")
- **Weight:** 50 gram.
- **Comm. Cable:** Shielded AWG gauge six conductor cable.



RBtec, innovator solution provider  
for perimeter intrusion detection systems.

In keeping with our policy of continuous development we reserve the right to alter these specifications without notice.