Compact 5000 MKII

Insurance Cash Rating £5,000 (Jewellery £50,000)



A range of safes in 8 sizes, suitable for the home and business premises

The overall body thickness is 50mm and the cavity between the inner and outer bodies includes bolt deflectors and is packed with a fire and burglary resistant monolith. Fire tested to BS476 Part 20.

The door plate is 10mm thick and the overall door thickness is 85mm. The bolt work has 28mm bolts that engage deep into the body of the safe with rear fixed dog bolts.

The bolt work is secured by a double bitted 8-lever keylock (certified to EN1300) and a live relocking device protected by a hardened drill resisting plate.

When the relocker moves into position, the safe is effectively locked in two different places.

Supplied standard: keylocking with 2 x keys, base fixing and 1 x adjustable shelf.

Locking Options include: mechanical (dial) combinations, electronic combinations, time locks, time delay locks and the facility for dual locking.



Model	External Dimensions			Internal Dimensions			Weight	Volume
	H (mm)	W (mm)	D (mm)	H (mm)	W (mm)	D (mm)	KG	LTR
COM00	380	328	359	280	228	222	87	14.5
COMO	405	532	486	305	432	349	160	46
COM1	481	430	429	381	330	292	150	36.5
COM2	608	430	429	508	330	292	170	49
COM3	735	532	556	635	432	419	275	115
COM4	862	557	594	762	457	457	318	159
COM5	989	608	645	889	508	508	395	229
COM6	1370	608	645	1270	508	508	525	328

*Cash ratings are guide lines only. Please check with your insurance company, **Please note that external depths do NOT include handle and hinges (please allow an extra 65mm). All weights and sizes are approximate and Dudley Safes Ltd reserves the right to change specifications without notice. Colour is flake grey unless otherwise specified. For dimensions of the safe with the door open, please visit www.dudleysafes.com/support.aspx