

Dudley Mark II Safe

Insurance Cash Rating £4,000 (Jewellery £40,000)



A cost effective range of safes available in 8 sizes with an enhanced 50mm cavity body construction, with an overall door thickness of 76mm.

Suitable for domestic and medium commercial applications.

Fire tested to BS476 Part 20 with added drill and fire resistance. The two-way boltwork is protected by a live relocker.

Supplied as standard with a double bitted keylock (certified to EN1300) with two keys, base fixing and one adjustable shelf.

LOCKING OPTIONS INCLUDE: Keyless combination; electronic combination and the facility for dual locking if required, time locks and time delay locks.



Model	External Dimensions			Internal Dimensions			Weight	Volume
	H (mm)	W (mm)	D (mm)	H (mm)	W (mm)	D (mm)		
D00	380	328	359	280	228	222	83	14.5
D1	481	430	429	381	330	292	138	36.5
D2	608	430	429	508	330	292	164	49
D3	735	532	556	635	432	419	265	115
D4	862	557	594	762	457	457	298	159
D5	989	608	645	889	508	508	370	229
D6	1370	608	645	1270	508	508	499	328
D7	1600	608	645	1500	508	508	577	393

*Cash ratings are guide lines only. Please check with your insurance company.**Please note that external depths do NOT include handle and hinges (please allow an extra 65mm). All weights and sizes are approximate and Dudley Safes Ltd reserves the right to change specifications without notice. Colour is flake grey unless otherwise specified. For dimensions of the safe with the door open, please visit www.dudleysafes.com/support.asp