

Harlech Lite S2

Insurance Cash Rating £4,000 (Jewellery £40,000)



A range of lightweight safes available in 8 sizes, suitable for domestic and small commercial risks. The range is well designed and complies with the requirements of EN14450 and is tested and certified by the LPCB.



The body is constructed with 50mm cavity and is fitted with a solid steel plate door. The overall door thickness is 76mm.

The boltwork is secured by a high-security, double-bitted keylock as standard (other options are available) and is certified to EN1300.

Fire tested to BS476 Part 20.

The Level 2 range is further protected by a live relocker and internal body deflectors.

Supplied as standard keylock (certified to EN1300) with two keys, dual base fixing and one adjustable shelf. Locking Options: Keyless combination; electronic combination and the facility for dual locking if required and time delay locks.



Model	External Dimensions			Internal Dimensions			Weight	Volume
	H (mm)	W (mm)	D (mm)	H (mm)	W (mm)	D (mm)		
HL2-00	380	328	359	280	228	222	31	14.5
HL2-0	405	532	486	305	432	349	51	46
HL2-1	481	430	429	381	330	292	48	36.5
HL2-2	608	430	429	508	330	292	56	49
HL2-3	735	532	556	635	432	419	83	115
HL2-4	862	557	594	762	457	457	87	159
HL2-5	989	608	645	889	508	508	126	229
HL2-6	1370	608	645	1270	508	508	159	328

*Cash ratings are guide lines only. Please check with your insurance company.**Please note that external depths do NOT include handle and hinges (please allow an extra 65mm). All weights and sizes are approximate and Dudley Safes Ltd reserves the right to change specifications without notice. Colour is flake grey unless otherwise specified. For dimensions of the safe with the door open, please visit www.dudleysafes.com/support.aspx